

Prior Solvent E

Product information

2019-11-22/MDS/JF Copyright©

Product type

- Water-rinsable cold degreaser.
- Oil, tar and wax remover.

What to use the product for?

- Cleaning of oil and grease-contaminated machinery, tools, interiors, floors, etc.
- Removal of adhesive residue from sticky labels.
- Dissolution of rust treatment products, for example stains on textiles.
- Dewaxing of new cars.
- Removal of bitumen.
- Cold degreasing in cleaning tanks/parts washer.

Product advantages

- Effective dissolution of oil, grease, wax and bitumen.
- Can be rinsed off with water.
- Low odour.
- Aids fast separation in oil separator.
- Free of aromatics.
- High flash point – low evaporation.
- Easily biodegradable.

Working solution

- Use undiluted

Water-rinsable cold degreaser.

May air dry.

Dissolves tar, wax, glue, oil, soot and grease.



How to use the product

- Oil and grease-contaminated parts:
Apply with a brush or low-pressure sprayer.
Leave to work for about 10 minutes.
Rinse with cold or hot water. It is fastest to rinse with hot water.
- Dewaxing:
Apply Prior Solvent E to the wax-protected surfaces.
Pour a couple of litres in a bucket and wash with a soft brush or sheepskin wash mitt until the wax layer has loosened completely from the paintwork.
Use a pressure washer to rinse with hot water.
Can also be rinsed manually with water and a brush.
- Adhesive residue:
Dab or spray onto the adhesive. Leave to work for 5–10 minutes until the adhesive has softened.
Scrape or wash off.
- Surfaces that may come into contact with foodstuffs must be rinsed thoroughly with clean water.

Technical information

- Read the safety data sheet before use.

MAL-code:

- MAL code: 1-1 (1993)